Eurolift
ASCENSEURS

Lift with machine room

Lift with machine room

320 to 630 kg | 4 to 8 persons | 1 m/s | 1:1 roping



The geared machine sits in a technical room above the shaft. A robust, proven solution that is easy to maintain.

LIFT WITH MACHINE ROOM

Lift with machine room

The geared machine sits in a technical room above the shaft. A robust, proven solution that is easy to maintain.

Key benefits

Robust

A proven technology suited to intensive use.

Easy access

The drive is accessible in its room for simple maintenance.

Quiet

A vibration-free geared machine thanks to Sodimas technology.

Replacement

Ideal for modernising an existing lift that already has a machine room.

In pictures



Machinery in a machine room, above or below the shaft depending on your building.



Direct or 2:1 roping, geared machine or gearless motor.



Sodimas QI Touch or Edel K2 Advanced controller.

Which buildings

- Buildings with a machine room
- Lift modernisation
- High-rise buildings
- Intensive use

LIFT WITH MACHINE ROOM

Standard configurations

	320 kg	450 kg	630 kg
Persons	4	6	8
Speed	1 m/s	1 m/s	1 m/s
Cabin (W × D)	1000 × 900 mm	1000 × 1200 mm	1100 × 1400 mm
Clear opening (W × H)	700 × 2000 mm	800 × 2000 mm	800 × 2000 mm
Shaft (W × D)	1400 × 1400 mm	1600 × 1600 mm	1700 × 1800 mm
Pit	1100 mm	1100 mm	1100 mm
Headroom	3600 mm	3600 mm	3600 mm
Roping	1:1	1:1	1:1

Other loads, speeds, dimensions and numbers of floors on request.

Standard equipment

- Sodimas QI Touch or Edel K2 Advanced controller
- Automatic 2-panel car and landing doors with variable-frequency operator
- M3 car operating panel in silver or gold, 4" TFT colour display
- Position indicators on every floor and load weighing
- LED shaft lighting
- Automatic rescue on UPS
- Compliance: Directive 2014/33/EU, standards EN 81-20, EN 81-50 and EN 81-28

Contact

France, French-speaking countries and Europe

WhatsApp +33 7 71 59 46 00

English- and Arabic-speaking countries · Dubai

WhatsApp +971 54 386 1511

contact@euro-lift.fr · **euro-lift.fr**